



FOR NOISY ROOMS WITH LIMITED WALL SPACE

Acoustic **Fabric Clouds** by NetWell are fabric wrapped fiberglass acoustic panels that float from the ceiling rather than flush mount to a surface.

Fabric Clouds are a popular choice for noisy rooms where wall space is limited. An added benefit with suspended panels is that both sides are exposed to the room, which increases sound absorption and improves acoustical performance.





controlnoise.com/fabric-clouds

FEATURES:

- Excellent acoustical performance
- High-quality, economical, multi-purpose panels
- · Class A fire rated
- Standard, designer or C.O.M. fabrics
- · Various mounting options
- · Custom sizes and shapes

APPLICATIONS:

- Libraries
- Restaurants
- Club rooms
- Ballrooms
- · School auditoriums

PHONE: 1-800-638-9355 EMAIL: help@controlnoise.com WEB: www.controlnoise.com



EDGE DETAIL

Edges are available in natural or chemically hardened edge.

SIZING

All panels are custom made with sizing up to a maximum 4'x10' and with thickness ranging from 1/2" – 2" thick.

FINISHES

Guilford of Maine FR701 Style 2100 is the industry standard. Hundreds of approved decorative fabrics are also available from numerous manufacturers including, but not limited to: Guilford of Maine,



Maharam, Design Tex and Knoll. Customers may also specify their own fabric, provided the material meets manufacturing requirements.

ACOUSTICAL PERFORMANCE

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
1/2"Thick	0.12	0.48	0.71	0.77	0.71	0.58	0.65
1"Thick	0.13	0.24	0.77	1.08	1.15	1.07	0.80
2″Thick	0.22	0.81	1.24	1.30	1.21	1.16	1.15

Tested as Type "E" Mounting

HARDWARE & INSTALLATION

FABRIC CLOUD MOUNTING OPTIONS

- Rotofast Cloud Anchors (A)
- D-Rings (B)

Note: Larger clouds may require T-grid attachment (included) to add structural rigidity. For more detailed installation instructions and a video, visit **controlnoise.com/installation**.

