

BLUSH PANELS

PAINTABLE ACOUSTICAL PANELS



ABSORB SOUND WITH CUSTOM COLOR MATCHING

Blush Panels by NetWell are the perfect solution where a traditional fabric finish is not desired. The acoustically transparent, paintable finish blends well with finished drywall to create a space absent of echo and reverberation. Rather than a textured finish of fabric, these panels provide an understated, more discreet acoustic finish within a space.

Blush Panels are part of a Class A rated system tested per ASTM E-84. In standard natural white or any standard paint color, Blush Panels provide the absorption required to create an acoustically correct space.



FEATURES:

- Excellent acoustical performance
- Class A fire rated per ASTM E-84
- Type A mount (wall panels),
Type E-400 mount (ceiling tiles)
- Custom sizes and shapes

APPLICATIONS:

- Schools/universities
- Auditoriums
- Houses of worship
- Office spaces

controlnoise.com/blush-panels



SIZING

Blush Panels are custom made with standard sizes up to 4' x 10' with 1" and 2" thicknesses.

EDGE DETAIL

A chemically hardened edge is required.



Square

ACOUSTICAL PERFORMANCE

| 1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies | | | | | | | |
|---|------|------|------|------|------|------|------|
| Frequency (Hz) | 125 | 250 | 500 | 1K | 2K | 4K | NRC |
| 1" Wall Panel | 0.09 | 0.39 | 0.87 | 1.05 | 1.04 | 0.88 | 0.85 |
| 2" Wall Panel | 0.54 | 0.82 | 1.16 | 1.12 | 1.03 | 0.94 | 1.05 |

* Panels are also available with 1/8" High Impact Facing if required.

HARDWARE AND INSTALLATION

BLUSH PANEL MOUNTING OPTIONS

- Impaling Clips (A)
- Rotofast Snap-On Anchors (B)
- Z-Clips + Wall Brackets (choice of 3" or panel-width) (C)

For more detailed installation instructions, visit our installation page at controlnoise.com/installation.

